



# Desk/3500

# Accept any payment at the counter

- Make NFC payments a seamless consumer experience
- Comply with the most stringent security requirements

















The Desk/3500 is PCI-PTS 5.x Certified.

# All payment options

The Desk/3500 enables NFC couponing and wallet use cases in addition to EMV Chip & PIN, swipe and contactless payments.

# User-friendly and intuitive interface

Featuring intuitive card readers and an easy-to-use applications menu, the Desk/3500 provides an enhanced payment experience.

# Maximized network availability

In addition to Ethernet and modem, the Desk/3500 offers Wi-Fi. Network availability and communication costs are fully optimized.

# Convenient NFC payment

The Desk/3500 boosts NFC payment by offering customers a seamless experience through a conveniently located card-reader zone and faster transaction flows.

# Secure payment from the Telium TETRA OS

Backed by 30 years of experience and its user-friendly interface, the Telium TETRA OS embeds the best security mechanisms to protect transaction privacy and leverage Ingenico Group's unique portfolio of payment applications.

# Eco-designed products

Ingenico Group follows a proactive eco-design policy. From design to production and market launch to recycling, we strive to minimize our environmental footprint throughout the product life cycle.









NAME			Desk/3500
Processor	Application & crypto processor	Cortex A5	•
Memory	Internal	256 MB Flash / 128 MB RAM	•
os		Telium TETRA OS	•
SAM		2	•
Card Readers	Magstripe Smart card Contactless	ISO 1/2/3, 500K lifespan EMV Level 1, 500K lifespan EMV Level 1 compliant	•
Display	Color	2.8" display, backlit, QVGA (320x240 pixels)	•
Keypad		20 ergonomic keys, raised marking, backlit	•
Audio	Buzzer		•
Thermal Printer	Speed in lines/s Paper roll cage	20 lines/s 58 mm width x Ø 40 mm	•
Terminal Connectivity	Wireless Wired	Wi-Fi Dial-up modem Ethernet 10/100 base T	Optional
Terminal Connections	USB Power supply Serial	1 USB Host 1 USB Slave Dedicated power jack 1 RS232	•
Power Supply		24W	•
Terminal Size		7.3 x 2.6 x 3.2" (187x82x68 mm)	•
Weight		12 oz (340 g)	•
Environment	Operating temperature Storage temperature Operating humidity	32°F to 104°F (0°C to +40°C) -4°F to 131°F (-20°C to +55°C) 85% non-condensing at 104°F (+40°C)	•
Accessory	Magic box Privacy shield	1x RS + 1x power + 1x ethernet +1x Line-In Field upgradable	•
Security		PCI-PTS 5.x	•



